



Specifications	Scag Freedom Z	Big Dog Stout	Gravely ZT XL HD	Hustler Raptor SD	John Deere Eztrak Z645, Z625, Z655
<b>Engine</b>	o 22hp & 24hp Kohler 7000 Series	o 21.5hp, 23hp & 24hp Kawasaki FR	o 23hp or 24hp Kawasaki FR o 24hp, 25hp or 26hp Kohler 7000 Series	o 22hp & 25hp Kohler 700 Series	o 24hp Kawasaki FS o 25hp Briggs Cyclonic
<b>Cutter Deck Size</b>	48" & 52"	48", 54" & 60"	44", 48", 52", 60"	36", 48" & 60"	48" & 50"
<b>Ground Speed</b>	8mph forward, 5mph reverse	8mph forward, 4mph reverse	8mph forward, 4mph reverse	7.5mph forward	9 mph forward, 4.5mph reverse
<b>Drive System</b>	o Dual Hydro-Gear ZT2800 with charge pumps	Dual Hydro-Gear ZT3100	Dual Hydro-Gear ZT3100	Dual Hydro-Gear ZT2800	Tuff Torq TZT 7 - M
<b>Steering Controls</b>	Dual adjustable levers	Dual levers	Dual levers adjustable	Dual levers, adjustable	Dual adjustable levers
<b>PTO Engagement</b>	Ogura electric clutch, adjustable air-gap	Electric clutch; non-adjustable	Ogura GT1A electric clutch	Electric Warner	Warner Mag-Stop electric clutch, non-adjustable 125ft.lb
<b>Fuel Capacity</b>	6.5 gallon, single tank	5 gallon, single tank	6 gallons	3 gallons	o 3.5 gal, single tank
<b>Drive Tires</b>	20 x 10 - 8	o 22 x 9.5 - 10 (48) o 22 x 11 - 10 (54/60)	20 x 10 - 10	o 20 x 8 - 10 (36/42) o 20 x 12 - 10 (54/60)	23 x 10.5 - 12
<b>Front Tires</b>	11 x 4.5 - 5, ribbed tread	o 13 x 5 - 6 (48) o 13 x 6.5 - 6 (54/60)	13 x 5 - 6, smooth tread	o 13 x 5 - 6 (36/42) o 13 x 6.5 - 6 (54/60)	13 x 6.5 - 6
<b>Deck Construction</b>	10-gauge top with 11-gauge reinforcement throughout spindle area, 7-gauge skirt; welded	10 ga. Fabricated w/ reinforced 11 ga. spindle mounts	10 gauge, welded, with .25" spindle reinforcement	11 gauge, fabricated with 7 gauge spindle reinforcement	Stamped; 9-12 gauge depending on model
<b>Deck Lift System</b>	Foot pedal with spring-assist	Foot pedal	Adjustable foot operated	Foot operated	Arm lever lift
<b>Cutting Height</b>	o 1" to 4.5" in .25" increments (48") o 1" to 5" in .25" increments (52")	1.5" to 4.5" in .25" increments	1" to 5"	1" to 4.5" in .25" increments	1" to 4"
<b>Cutter Deck Spindles</b>	Aluminum housing, sealed ball bearings, "maintenance-free", 1" steel shaft	Aluminum housing, steel shaft & sealed ball bearings	Cast-iron housing, sealed ball bearings, 1" shaft	Aluminum w/ 1.0" shafts and sealed ball bearings with double lip seals	Data not provided
<b>Seat</b>	Adjustable with armrests, thick cushioned, tan	Bolstered Seat, with embroidered logo, and internal suspension	High back with seat springs & lever adjust	Bolstered Seat, with thick bolstered armrests	21-in high-back seat with standard suspension and armrests
<b>Cupholder</b>	Standard	Standard	Standard	Standard	Standard
<b>Storage Compartment</b>	Standard	not available	No	No	Standard
<b>Foot Plate</b>	Pierced, extruded steel tread for permanent non-slip traction	Pierced, extruded steel tread for permanent non-slip traction	Pierced metal tread, flip up	Pierced metal tread	Pierced metal tread, flip-up
<b>Weight</b>	745-765 lbs	835 / 860 / 885 lbs.	800-853 lbs	586 - 685 lbs.	735-755 lbs.
<b>ROPS</b>	Standard	Standard, foldable	not available	not available	not available
<b>Warranty</b>	3-year / 500-hour non-commercial* 1-year commercial* *See Scag Freedom Z warranty statement for complete details.	7-year limited warranty	3-yr consumer limited warranty 1-yr commercial limited warranty 5-yr frame and deck shell warranty	3-yr / 300 hour limited warranty	4-yr / 500-hrs



Specifications	Scag Freedom Z	Simplicity ZT3500	eXmark Pioneer E-Series	Toro Titan MX	Bad Boy ZT Elite
<b>Engine</b>	o 22hp & 24hp Kohler 7000 Series	o 25hp Briggs & Stratton Commercial Turf Series	o 22hp Kohler Confidant EZT	o 21hp, 23hp, & 25hp Kohler Confidant	o 24hp Kawasaki FR o 22hp & 25hp Kohler 7000 Series
<b>Cutter Deck Size</b>	48" & 52"	48"	48" & 52"	48", 54" & 60"	48", 54" & 60"
<b>Ground Speed</b>	8mph forward, 5mph reverse	8mph forward, 4mph reverse	7mph forward, 4mph reverse	8.5mph forward	7mph forward
<b>Drive System</b>	o Dual Hydro-Gear ZT2800 with charge pumps	Dual Hydro-Gear ZT2800	Dual Hydro-Gear ZT2800 with charge pumps	Dual Hydro-Gear ZT2800 with charge pumps	Dual Hydro-Gear ZT3100
<b>Steering Controls</b>	Dual adjustable levers	Dual levers	Commercial Grade High Back contoured foam padded with armrests. Hinged mounting, spring suspension. Adjustment: Fore and aft from Operators' Position.	Dual levers w/ gas dampeners	Dual Hydro-Gear ZT3100
<b>PTO Engagement</b>	Ogura electric clutch, adjustable air-gap	Electric clutch, non-adjustable	Warner Mag-Stop electric clutch, non-adjustable 175ft-lb	Mag-Stop Electric PTO	Electric clutch, non-adjustable
<b>Fuel Capacity</b>	6.5 gallon, single tank	5.5 gal, single tank	7 gal, single tank	5 gallons	5.5 gallons
<b>Drive Tires</b>	20 x 10 - 8	20 x 10	o 20 x 8 - 10	20 x 8	22 x 11 - 10 turf tread
<b>Front Tires</b>	11 x 4.5 - 5, ribbed tread	11 x 4 - 5, smooth tread	13 x 5 - 6, smooth tread	11 x 4	13 x 6.5 - 6 smooth tread
<b>Deck Construction</b>	10-gauge top with 11-gauge reinforcement throughout spindle area, 7-gauge skirt; welded	10 gauge, fabricated, with reinforced side skirts and leading edge	10-gauge top that is formed and welded with reinforcement/guard on leading edge.	10-gauge fabricated steel with front bumper	3/16" Thick Solid Steel
<b>Deck Lift System</b>	Foot pedal with spring-assist	Foot pedal with rubber grip	Standard; foot-controlled deck lift	Foot pedal	Instant Lift Electronic Actuator
<b>Cutting Height</b>	o 1" to 4.5" in .25" increments (48") o 1" to 5" in .25" increments (52")	1.5" to 4.5"	1.5" to 5" in .25" increments	1.5" to 4.5"	1.5" to 4" with deck height control system
<b>Cutter Deck Spindles</b>	Aluminum housing, sealed ball bearings, "maintenance-free", 1" steel shaft	Data not provided	No maintenance, sealed and non-greasable spindles; 7.50"-diameter cutter housing contains 17mm (.67")diameter spindle shaft and hex blade drive.	7.75 in (19.68 cm) diameter housing / 1 in (2.54 cm) diameter shaft	Cast-iron sealed ball bearings
<b>Seat</b>	Adjustable with armrests, thick cushioned, tan	High back adjustable w/o armrests, black	Commercial Grade High Back contoured foam padded with armrests. Hinged mounting, spring suspension. Adjustment: Fore and aft from Operators' Position.	Deluxe Bolstered Seat w/ Adjustable Suspension	Flip up, thick foamed black with adjustable armrests
<b>Cupholder</b>	Standard	Standard	Standard	Standard	Standard
<b>Storage Compartment</b>	Standard	Standard	No	Yes (tool box)	Standard
<b>Foot Plate</b>	Pierced, extruded steel tread for permanent non-slip traction	Rubber/plastic sheet tread	Pierced metal tread	Pierced metal tread	Rubber pad
<b>Weight</b>	745-765 lbs	724 lbs	799 to 805 lbs	Data not provided	804 / 831 / 858 lbs.
<b>ROPS</b>	Standard	not available	Standard, foldable	Standard, foldable	not available
<b>Warranty</b>	3-year / 500-hour non-commercial* 1-year commercial* *See Scag Freedom Z warranty statement for complete details.	3-yr limited residential 90-day limited commercial Lifetime mower deck	2-yr commercial & 4-yr residential (E Series) 1-yr commercial & 4-yr residential (S Series)	4 Year Limited / 400 hr Frame Guaranteed for Life	2-year drive, spindle and clutch system warranty