



Specifications	Scag Patriot	Ferris 700Z	Hustler FasTrak
Engine Options:	o 22hp Kawasaki FX o 22hp Kawasaki FX	o 23hp & 23.5hp Kawasaki FS o 26hp Briggs Vanguard o 27hp Briggs Commercial Turf	o 23hp & 24hp Kawasaki FR Series
Ground Speed*:	o Forward: 8.5MPH (52") 10MPH (61") o Reverse: 5MPH	10MPH forward, 5MPH reverse	8MPH forward
Cutter Deck Sizes:	52" & 61"	52" & 61"	48", 54" & 60"
Main Frame Construction:	Single tube, steel frame, full length, fully welded	Single tube, steel frame, full length, fully welded	1.5" x 3" steel tubes form the core of this frames' strength and durability. It's backed by a lifetime warranty.
Drive Tires:	22 x 9.5 - 12 pneumatic	22 x 11 -10	o 22 x 9.5 - 10 (48) o 22 x 11 - 10 (54/60)
Caster Tires:	o 13 x 5 - 6, 4-ply (52") o 13 x 6.5 - 6, 4-ply (61")	13 x 5 - 6	o 13 x 5 - 6 (48) o 13 x 6.5 - 6 (54/60)
Drive System:	o Hydro-Gear ZT3100 (52") o Hydro-Gear ZT3400 (61")	Hydro-Gear ZT3400	Hydro-Gear ZT3100
Caster Wheel Bearings:	Maintenance-free igus® iglide® polymer sleeve bearings; dual sealed ball bearings in caster wheel pivots	Not reported	Not reported
Steering Controls	Dual adjustable levers	Dual adjustable levers	Dual adjustable levers
PTO Engagement	Ogura electric clutch, adjustable air-gap	Not reported	Electric PTO Clutch
Fuel Capacity	6.5 gallon, single tank	5.5 gallon, single tank	5 gallon, single tank
Deck Construction	Dual-plate construction consists of a 10-gauge steel cutter deck top reinforced with an 11-gauge spindle support plate. Deck skirt is 7-gauge.	iCD™ Cutting System with professional lawn striper	10 gauge fabricated reinforced with 11 gauge at spindles. Front impact bar 3/8" x 1" steel
Deck Lift System	Foot pedal with spring-assist	Foot pedal	Foot operated deck height adjustment and a simple height selection system.
Cutting Height	1" to 5" in .25" increments	1" to 5" in .25" increments	1.5" to 4.5"
Cutter Deck Spindles	Aluminum housing, sealed ball bearings, "maintenance-free", 1" steel shaft	Cast-aluminum greaseable spindles feature 1" shaft with 2.5" x 1" dual ball bearings with top access grease fittings and pressure relief valve.	Aluminum w/ 1.0" shafts and double lip sealed ball bearings
Seat	Adjustable with armrests, ultra-plush, bolstered seat	Mid-back seat with armrests	Custom, bolstered vinyl seat with internal suspension for superior comfort.
Cupholder	Standard	Standard	Standard
Storage Compartment	Standard	No	Standard
Foot Plate	Rubber iso-mounted for comfort; pierced, extruded steel tread for permanent non-slip traction	Rubber mat on flip up platform	Pierced and extruded steel, flip up
Weight	840 lbs. - 900 lbs.	1059 - 1113 lbs.	835 - 885 lbs.
ROPS	Low-profile, foldable Roll-Over Protection System (ROPS).	Standard, 180° foldable	Standard, foldable
Warranty	2-year commercial or 3-year / 500-hour non-commercial mower warranty	4-year / 500 hour	4-year / 400 hour



Specifications	Scag Patriot	Toro 2000	eXmark Lazer S-Series (select)
Engine Options:	o 22hp Kawasaki FX o 22hp Kawasaki FX	o 20.5hp, 22hp Kawasaki FX	o 22hp & 25.5 Kawasaki FX o 25hp Kohler Command Pro Non-EFI models only
Ground Speed*:	o Forward: 8.5MPH (52") 10MPH (61") o Reverse: 5MPH	8.5MPH forward	10MPH forward, 6MPH reverse
Cutter Deck Sizes:	52" & 61"	48" , 52" & 60"	52" & 60"
Main Frame Construction:	Single tube, steel frame, full length, fully welded	A commercial-grade carrier frame, constructed of 3" x 1.5" tubular steel, supports the cutting deck and stands up to the rigors of professional use.	Unibody, welded, heavy-duty 1.5" x 3" tubular steel.
Drive Tires:	22 x 9.5 - 12 pneumatic	o 22 x 9.5 - 12 (48/52) o 22 x 10.5 - 12 (60)	o 23 x - 9.5 - 12 (52) o 24 x - 12 - 12 (60)
Caster Tires:	o 13 x 5 - 6, 4-ply (52") o 13 x 6.5 - 6, 4-ply (61")	o 13 x 5 - 6 (48) o 13 x 6.5 - 6 (52/60)	o 13 x 5 - 6 (52) o 13 x 6.5 - 6 (60)
Drive System:	o Hydro-Gear ZT3100 (52") o Hydro-Gear ZT3400 (61")	Hydro-Gear ZT3400	Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 12 cc pumps and 14. 5 cubic inch motors.
Caster Wheel Bearings:	Maintenance-free igus® iglide® polymer sleeve bearings; dual sealed ball bearings in caster wheel pivots	Not reported	Not reported
Steering Controls	Dual adjustable levers	Dual adjustable levers	Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to 2 height positions.
PTO Engagement	Ogura electric clutch, adjustable air-gap	Not reported	MagStop electromagnetic 200-ft-lb clutch with spot brake
Fuel Capacity	6.5 gallon, single tank	8 gallon, single tank	12 gallons
Deck Construction	Dual-plate construction consists of a 10-gauge steel cutter deck top reinforced with an 11-gauge spindle support plate. Deck skirt is 7-gauge.	7/10-gauge, high-strength steel, TURBO FORCE® w/bull-nose bumper	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge formed and welded spindle mounting locations for improved strength and reduced weight.
Deck Lift System	Foot pedal with spring-assist	Foot pedal with spring-assist	Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.
Cutting Height	1" to 5" in .25" increments	1.5" to 5" in .25" increments	1" to 5" in .25" increments
Cutter Deck Spindles	Aluminum housing, sealed ball bearings, "maintenance-free", 1" steel shaft	Toro's rugged 8" aluminum spindle assemblies survive impacts that would destroy lesser spindles	No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft and splined blade driver.
Seat	Adjustable with armrests, ultra-plush, bolstered seat	Mid-back seat with armrests	Deluxe, two tone, bolstered seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.
Cupholder	Standard	Standard	Standard
Storage Compartment	Standard	Standard	Standard
Foot Plate	Rubber iso-mounted for comfort; pierced, extruded steel tread for permanent non-slip traction	Pierced and extruded steel, flip up	Pierced and extruded steel, flip up
Weight	840 lbs. - 900 lbs.	926 - 988 lbs.	1104 - 1177 lbs.
ROPS	Low-profile, foldable Roll-Over Protection System (ROPS).	Standard, foldable	2-post foldable ROPS standard with seat belt and latch.
Warranty	2-year commercial or 3-year / 500-hour non-commercial mower warranty	4 Year Limited / 400 hr Frame Guaranteed for Life	3 year limited commercial



Specifications	Scag Patriot	Bad Boy CZT Elite
Engine Options:	o 22hp Kawasaki FX o 22hp Kawasaki FX	o 24hp Kawasaki FS o 25hp Kohler Confidant o 26hp Briggs Commercial Turf
Ground Speed*:	o Forward: 8.5MPH (52") 10MPH (61") o Reverse: 5MPH	10MPH forward
Cutter Deck Sizes:	52" & 61"	48" , 54" & 60"
Main Frame Construction:	Single tube, steel frame, full length, fully welded	2 x 2 tube steel, single tube
Drive Tires:	22 x 9.5 - 12 pneumatic	23 x 10.5 - 12
Caster Tires:	o 13 x 5 - 6, 4-ply (52") o 13 x 6.5 - 6, 4-ply (61")	13 x 6.5 - 6
Drive System:	o Hydro-Gear ZT3100 (52") o Hydro-Gear ZT3400 (61")	Hydro-Gear ZT3400
Caster Wheel Bearings:	Maintenance-free igus® iglide® polymer sleeve bearings; dual sealed ball bearings in caster wheel pivots	Not reported
Steering Controls	Dual adjustable levers	Dual adjustable levers
PTO Engagement	Ogura electric clutch, adjustable air-gap	Not reported
Fuel Capacity	6.5 gallon, single tank	11 gallons
Deck Construction	Dual-plate construction consists of a 10-gauge steel cutter deck top reinforced with an 11-gauge spindle support plate. Deck skirt is 7-gauge.	3/16" thick solid steel
Deck Lift System	Foot pedal with spring-assist	Instant Lift Electronic Actuator
Cutting Height	1" to 5" in .25" increments	1.5" to 4" in .25" increments
Cutter Deck Spindles	Aluminum housing, sealed ball bearings, "maintenance-free", 1" steel shaft	Cast-iron sealed ball bearings
Seat	Adjustable with armrests, ultra-plush, bolstered seat	Flip up, thick foamed black with adjustable armrests
Cupholder	Standard	Standard
Storage Compartment	Standard	Standard
Foot Plate	Rubber iso-mounted for comfort; pierced, extruded steel tread for permanent non-slip traction	Rubber pad
Weight	840 lbs. - 900 lbs.	862 - 925 lbs.
ROPS	Low-profile, foldable Roll-Over Protection System (ROPS).	Standard, foldable
Warranty	2-year commercial or 3-year / 500-hour non-commercial mower warranty	