



Specifications	Tiger Cat	Tiger Cat II	Hustler X One	Toro Commercial 3000	eXmark LazerZ S-Series	Bad Boy Outlaw
<b>Engine Options:</b>	o 22hp Kawasaki FX o 26.5hp Kohler Command EFI	o 22hp Kawasaki FS o 22hp & 23hp Kawasaki FX o 23hp Kohler Command Pro o 25hp & 26hp Kohler Command Pro EFI	o 22hp, 23.5hp & 27hp Kawasaki FX o 28hp Briggs Vanguard EFI	o 20.5hp, 22hp & 23.5hp Kawasaki FX o 25hp Kohler Command Pro	o 20hp, 22hp & 25.5 Kawasaki FX o 25hp Kohler Command Pro o 25hp & 26hp Kohler Command Pro EFI o 25hp Kohler Command Pro Propane EFI	o 24hp Briggs Vanguard o 25hp Kohler Confidant o 25hp Kawasaki FX
<b>Ground Speed*:</b>	10mph forward, 4.5mph reverse	12mph forward, 5mph reverse	11 mph forward, 6 mph reverse	10 mph forward, 5 mph reverse	10MPH forward, 6MPH reverse	11mph forward
<b>Main Frame Construction:</b>	Single tube, steel frame, full length, fully welded	Single tube, steel frame, full length, fully welded	Welded steel tube: 1.5" x 2.0" x .188"	Welded steel tube with bolt-together sections	Unibody, welded, heavy-duty 1.5" x 3" tubular steel.	11 gauge 2" x 2" 4-Rail steel frame
<b>Drive Tires:</b>	o 52": 24 x 9.5 -12, 4 ply o 61": 24 x 12 - 12, 4 ply	o 24 x 9.5 - 12 (48/52) o 24 x 12 - 12 (61)	o 24 x 9.5 - 12 (48" & 54") o 24 x 12 - 12 (60")	o 24 x 12 - 12 (60/72) o 23 x 9.5 - 12 (48/52)	o 22 x 9.5 - 12 (48/52) o 22 x 10.5 - 12 (60)	24 x 12 - 12
<b>Caster Tires:</b>	o 13 x 5 - 6 (52"); pneumatic, 4-ply o 13 x 6.5 - 6 (61"); pneumatic, 4-ply	o 13 x 5 - 6 (48/52) pneumatic, 4-ply o 13 x 6.5 - 6 (61) pneumatic, 4-ply	13 x 6.5 - 6, ribbed, semi-pneumatic	o 13 x 5 - 6 (48) o 13 x 6.5 - 6 (52/60/72)	o 13 x 5 - 6 (48) o 13 x 6.5 - 6 (52/60)	13 x 6.5 - 6
<b>Caster Wheel Bearings:</b>	Tapered roller bearings	Tapered roller bearings	Ball bearings	Ball bearings	Ball bearings	Data not published
<b>Front Caster Arm Design:</b>	Bolt-on for easy replacement if necessary	Bolt-on for easy replacement if necessary	Not serviceable	Not serviceable	Not serviceable	Not serviceable
<b>Hydraulic Drive System:</b>	Dual Pumps; 10cc displacement, Hydro-Gear Dual Motors: Parker	Dual Pumps; 12cc displacement, Hydro-Gear Dual Motors: Parker	Dual Hydro-Gear 12cc Dual Parker TF0240 Motors	Unitized pumps and motors; 12cc pumps	Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 12 cc pumps and 14.5 cubic inch motors.	Dual Hydro-Gear 4400
<b>Hydraulic Oil Filter:</b>	10 micron	10 micron	40 micron	Data not published	Data not published	Internal, replaceable
<b>Belt Tensioning System:</b>	Self-adjusting, spring-loaded design	Self-adjusting, spring-loaded design	Spring-loaded, self-adjusting	Data not published	Spring-loaded, self-adjusting	Spring tension
<b>Belt Construction:</b>	Kevlar cord, commercial grade Dayco belts	Kevlar cord, commercial grade Dayco belts	V-belts	Aramid fiber "V" belts	Data not published	V-Belt
<b>Drive/Load Pulleys:</b>	Split-steel design, stronger and lighter weight than cast-iron	Split-steel design, stronger and lighter weight than cast-iron	Data not published	Data not published	Data not published --Some plastic pulleys?	Data not published
<b>Instrument Panel :</b>	Key switch, throttle, manual choke, BBC switch	Key switch, throttle, manual choke (non-EFI models), PTO switch, 12-Volt Outlet & Tiger Eye: Advanced Monitoring System	Key switch, throttle, manual choke, PTO switch	Key switch, throttle, manual choke, BBC switch	Throttle, PTO switch, choke, ignition switch, operational diagnostics with integral fuel gauge	Throttle, Hour Meter, PTO, Choke, Ignition, 12V Outlet
<b>Seat:</b>	Torsion spring suspension seat, adjustable with padded arm rests (most models)	o Torsion spring suspension seat, adjustable with padded arm rests (most models) o Soft-Ride seat on select models o Seats are 4-point iso-mounted	Adjustable vinyl seat with armrests	Premium Bolstered	Deluxe, two tone, bolstered seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft side and seat flip-up.	Heavy padded comfort seat with padded arm rests
<b>Travel Controls:</b>	Dual, large diameter, standard-style control levers	Dual, large diameter, standard-style control levers	Dual stick controls	Dual stick controls	Dual stick controls	Dual adjustable stick controls
<b>PTO - Electric Clutch:</b>	Ogura GT3.5 - 250 ft lb	Ogura GT3.5 - 250 ft lb	Warner Mag Stop, non-adjustable	Warner MagStop - 175 ft lb	MagStop electromagnetic 200-ft-lb clutch with spot brake	Warner Mag Stop, non-adjustable
<b>Cutter Deck Sizes:</b>	52" & 61" Velocity Plus deck	48", 52" & 61" Velocity Plus deck	48", 54" & 60" Offer in RD for 54/60	48", 52", 60" & 72"	48", 52", 60", & 72"	54" & 61"
<b>Cutter Deck Construction:</b>	Tri-Plate, welded, with 7 gauge deck shell, 10 gauge & 11 gauge reinforcement plates	Tri-Plate, welded, with 7 gauge deck shell, 10 gauge & 11 gauge reinforcement plates	7 gauge steel skirt with 11 gauge top and 11-gauge spindle reinforcements, steel bar reinforcement on trim edges	7 gauge steel, welded, reinforcements on bumper, discharge chute and side	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge formed and welded spindle mounting locations for improved strength and reduced weight.	1/4" thick steel 3 gauge construction with 3 gauge skirt
<b>Number of Anti-Scalp Wheels:</b>	4	4	3	o 48/52 = 3, 1 additional option o 60/72 = 4, 1 additional option	4	6 total, 4 in front 2 in rear



Specifications	Tiger Cat	Tiger Cat II	Hustler X One	Toro Commercial 3000	eXmark LazerZ S-Series	Bad Boy Outlaw
<b>Cutter Deck Spindles:</b>	Scag Heavy-Duty Spindles w/cast-iron housing, tapered roller bearings, & 1.125" shaft, backed by 3-year limited warranty	Scag Heavy-Duty Spindles w/cast-iron housing, tapered roller bearings, & 1.125" shaft, backed by 3-year limited warranty	Ductile iron housing, sealed ball bearings	Cast-iron housing, greaseable ball bearings, 1" shaft	No maintenance, sealed and non-greaseable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft and splined blade driver.	No maintenance sealed aluminum housing
<b>Cutter Deck Lift / Height Adjustment:</b>	Foot pedal lift with self-locking mechanism at transport position	Foot pedal lift with self-locking mechanism at transport position	Foot pedal lift	Adjustable hand lever, deck lift assist pedal	Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.	Foot pedal lift
<b>Parking Break:</b>	Hand lever	Foot pedal engages AUSCO disc breaks	Patented automatic	Hand Lever	Hand lever	Hand lever
<b>Cutting Range:</b>	1" to 5" in 1/4" increments	1" to 5" in 1/4" increments	1" to 5.5" in 1/4" increments	1" to 5.5" in 1/4 increments	1" to 5" in .25" increments	1" to 5.5"
<b>Fuel Capacity:</b>	7 gallons	9.5 gallons	10.3 gallons	8 gallons	12 gallons	13.8 gallons

All specifications subject to change without notice. Competitor specifications accurate to the best of our knowledge as of date of publication. Scag assumes no responsibility for accuracy or completeness of information.

\*Actual ground speeds may vary



Specifications	Tiger Cat	Tiger Cat II	Gravely Pro Turn 200	Ferris 2100 Series
<b>Engine Options:</b>	o 22hp Kawasaki FX o 26.5hp Kohler Command EFI	o 22hp Kawasaki FS o 22hp & 23hp Kawasaki FX o 23hp Kohler Command Pro o 25hp & 26hp Kohler Command Pro EFI	o 27hp & 31hp Kawasaki FX o 25hp Kohler ZT Confidant o 29hp Kohler Command Pro EFI	o 26hp & 28hp Briggs Vanguard o 32hp Briggs Vanguard Big Block o 25.5hp Kawasaki FX
<b>Ground Speed*:</b>	10mph forward, 4.5mph reverse	12mph forward, 5mph reverse	13mph forward, 6mph reverse	10mph forward; 6mph reverse
<b>Main Frame Construction:</b>	Single tube, steel frame, full length, fully welded	Single tube, steel frame, full length, fully welded	1.5" by 3" steel, singular tube frame	Single tube, steel frame, full length, fully welded
<b>Drive Tires:</b>	o 52": 24 x 9.5 -12, 4 ply o 61": 24 x 12 - 12, 4 ply	o 24 x 9.5 - 12 (48/52) o 24 x 12 - 12 (61)	24 x 12 - 12	o 24 x 9.5 - 12 (52) o 24 x 12 - 12 (61)
<b>Caster Tires:</b>	o 13 x 5 - 6 (52"); pneumatic, 4-ply o 13 x 6.5 - 6 (61"); pneumatic, 4-ply	o 13 x 5 - 6 (48/52) pneumatic, 4-ply o 13 x 6.5 - 6 (61) pneumatic, 4-ply	15 x 6 - 6	o 13 x 5 - 6 (52) o 13 x 6.5 - 6 (61)
<b>Caster Wheel Bearings:</b>	Tapered roller bearings	Tapered roller bearings	Data not published	Tapered roller bearings
<b>Front Caster Arm Design:</b>	Bolt-on for easy replacement if necessary	Bolt-on for easy replacement if necessary	Not serviceable	Bolt-on for easy replacement if necessary
<b>Hydraulic Drive System:</b>	Dual Pumps; 10cc displacement, Hydro-Gear Dual Motors: Parker	Dual Pumps; 12cc displacement, Hydro-Gear Dual Motors: Parker	Dual Hydro-Gear 5400	Hydro-Gear ZT4400
<b>Hydraulic Oil Filter:</b>	10 micron	10 micron	Data not published	Data not published
<b>Belt Tensioning System:</b>	Self-adjusting, spring-loaded design	Self-adjusting, spring-loaded design	CBT System: constant belt tension system	Self-adjusting, spring-loaded design system
<b>Belt Construction:</b>	Kevlar cord, commercial grade Dayco belts	Kevlar cord, commercial grade Dayco belts	Data not published	Data not published
<b>Drive/Load Pulleys:</b>	Split-steel design, stronger and lighter weight than cast-iron	Split-steel design, stronger and lighter weight than cast-iron	Data not published	Data not published
<b>Instrument Panel :</b>	Key switch, throttle, manual choke, BBC switch	Key switch, throttle, manual choke (non-EFI models), PTO switch, 12-Volt Outlet & Tiger Eye: Advanced Monitoring System	PTO switch, hour meter, key switch, throttle & choke	PTO switch, hour meter, key switch, throttle & choke
<b>Seat:</b>	Torsion spring suspension seat, adjustable with padded arm rests (most models)	o Torsion spring suspension seat, adjustable with padded arm rests (most models) o Soft-Ride seat on select models o Seats are 4-point iso-mounted	High-Back w/ full suspension	Self-adjusting, spring-loaded design. Flip-up
<b>Travel Controls:</b>	Dual, large diameter, standard-style control levers	Dual, large diameter, standard-style control levers	Dual Stick	Dual adjustable stick controls
<b>PTO - Electric Clutch:</b>	Ogura GT3.5 - 250 ft lb	Ogura GT3.5 - 250 ft lb	Ogura GT3.5	Warner Electric
<b>Cutter Deck Sizes:</b>	52" & 61" Velocity Plus deck	48", 52" & 61" Velocity Plus deck	52", 60" & 72"	52" & 61"
<b>Cutter Deck Construction:</b>	Tri-Plate, welded, with 7 gauge deck shell, 10 gauge & 11 gauge reinforcement plates	Tri-Plate, welded, with 7 gauge deck shell, 10 gauge & 11 gauge reinforcement plates	7-gauge fabricated and welded deck with .25" reinforcement at spindles	iCD™ Cutting System with professional lawn striper.
<b>Number of Anti-Scalp Wheels:</b>	4	4	6 total, 4 in front 2 in rear	6 total



Specifications	Tiger Cat	Tiger Cat II	Gravely Pro Turn 200	Ferris 2100 Series
<b>Cutter Deck Spindles:</b>	Scag Heavy-Duty Spindles w/cast-iron housing, tapered roller bearings, & 1.125" shaft, backed by 3-year limited warranty	Scag Heavy-Duty Spindles w/cast-iron housing, tapered roller bearings, & 1.125" shaft, backed by 3-year limited warranty	Ball bearing, Cast Iron w/ steel shaft	Features cast-iron greaseable (61" model shown) or aluminum greaseable (52") spindles
<b>Cutter Deck Lift / Height Adjustment:</b>	Foot pedal lift with self-locking mechanism at transport position	Foot pedal lift with self-locking mechanism at transport position	Foot pedal lift	Foot pedal lift
<b>Parking Break:</b>	Hand lever	Foot pedal engages AUSCO disc breaks	Park of hand controls	Hand Lever
<b>Cutting Range:</b>	1" to 5" in 1/4" increments	1" to 5" in 1/4" increments	1" to 5.5" in .25" increments	1.75" to 5" in .25" increments
<b>Fuel Capacity:</b>	7 gallons	9.5 gallons	13.4 gallons	11 gallons

All specifications subject to change without notice. Competitor specifications accurate to the best of our knowledge :  
 \*Actual ground speeds may vary